

Section 1 - Identification

Product Name: Kiara Sky Dip Essential Seal Protect - .5oz, 2oz

Product Sku: KSDSP01, DERSP2OZ

Company: **Kiara Sky Professional Nails Inc.**
8700 Swigert Ct. Ste. 109-209
Bakersfield, CA 93311

Company Number: (661)393-4800

Emergency Contact: CHEMTEL **Contract:** MIS2294037

Emergency Phone: (800)255-3924 **Outside of U.S.:** (813)248-0585

Section 2 - Hazards Identification

GHS classifications

Health: Target Organ Toxicity (Single exposure), Category 3
Serious Eye Damage/Eye Irritation, Category 2A
Acute Toxicity (Oral), Category 4

Physical: Flammable Liquids, Category 2

GHS label elements

Hazard pictograms:



Signal Word: DANGER

Hazard statements: H225: Highly flammable liquid and vapor.
H302: Harmful if swallowed.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

Precautionary statements

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground and bond container and receiving equipment.
P242: Use non-sparking tools.
P243: Take action to prevent static discharges.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P264: Wash skin and hands thoroughly after handling.
P270: Do not eat, drink, or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P330: Rinse mouth.
P337+P313: If eye irritation persists: Get medical advice/attention.
P370+P378: In case of fire: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment for extinction.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P403+P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

Section 3 - Composition/Information on Ingredients

Chemical Name	CAS number:	%
Ethyl Acetate	141-78-6	85 - 100
Methyl propyl ketone	107-87-9	< 1
Methyl-Isobutyl Ketone	108-10-1	< 1
N,N-DIMETHYL-P-TOLUIDINE	99-97-8	< 1

Section 4 - First Aid Measures

Description of necessary first aid measures

Eye contact:

Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

Skin contact:

Wash with soap and water. Get medical attention if irritation develops or persists.

Ingestion:

If swallowed, seek medical advice immediately and show this container or label.

Inhalation:

Remove to fresh air. Get medical attention if breathing is difficult.

Over-exposure signs/symptoms

Acute Effects:

Vapors may be irritating to eyes, throat and mucous membranes; ingestion may cause headache, drowsiness and possible unconsciousness.

Section 5 - Fire-fighting measures

General Hazard:

Highly flammable. Irritant.

Extinguishing media:

Use dry chemical, foam or carbon dioxide.

Explosion Hazards:	Vapors can travel to a source of ignition and flash back.
Fire fighting procedures:	Avoid using large quantities of water.
Fire fighting equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, (OSHA approved or equivalent) and full protective gear.
Hazardous decomposition products:	Carbon monoxide or carbon dioxide.

Section 6 - Accidental release measures

Methods and materials for containment and cleaning up

Large spill:

Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on adsorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal.

Environmental precautions

Water spill: This product is readily biodegradable. Do not release into surface waters.

Section 7 - Handling and storage

Precautions for safe handling

General procedures:

Avoid breathing of vapors. Use only in well ventilated areas. When handling, do not eat, drink or smoke.

Section 8 - Exposure controls/personal protection

Exposure guidelines

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		Exposure limits			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m3	ppm	mg/m3
Ethyl acetate	TWA	400	1400	400	1440
	STEL	-	-	75	-
Methyl-Isobutyl Ketone	TWA	100	410	20	-
	STEL	-	-	75	-
N,N-DIMETHYL-P-TOLUIDINE	TWA	0.50	No data available	No data available	No data available
	STEL	No data available	No data available	No data available	No data available

Personal protective measures

Eyes and face:	Avoid contact with eyes.
Skin:	Wear suitable gloves.
Respiratory:	Use only in a well-ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment. Recommended: Full-face OSHA-approved respirator with organic vapor cartridge.

Section 9 - Physical and chemical properties

Appearance

Physical state:	Liquid.
Odor:	Strong fruity odor.
Odor threshold:	No data available
Appearance:	Clear, Colorless liquid
Color:	Clear to pale yellow
pH:	No data available
Percent volatile:	No data available
Flash point and method:	1.11°C (30°F) TCC
Flammable limits:	2 to 11.4
Auto-ignition temperature:	427°C (800.6°F)
Vapor pressure:	73 mmHg at 20°C (68°F)
Vapor density:	No data available
Boiling point:	77°C (170°F) to 78°C (172°F)
Freezing point:	No data available
Melting point:	Not Established
Thermal decomposition:	No data available
Solubility in water:	Slightly soluble.
Evaporation rate:	4.5 (n-Butyl Acetate=1)
Specific gravity:	0.9 (water=1)
Viscosity #1:	< 5 Centipoise
(VOC):	9 g/L

Section 10 - Stability and reactivity

Hazardous polymerization:	No
Conditions to avoid:	Heat, sparks and flame.
Hazardous decomposition products:	Carbon monoxide, dioxide.
Incompatible materials:	Strong oxidizing agents, acids and bases.

Section 11 - Toxicological information

Acute

Chemical name	Oral LD ₅₀ (rat)	Dermal LD ₅₀ (rabbit)	Inhalation LC ₅₀ (rat)
Ethyl acetate	5620 mg/kg (rat)	180,000 mg/kg (rabbit)	45,000 mg/m ³ (mouse, 2hr)
Methyl propyl ketone	1600 mg/kg	> 20 mg/kg (guinea pig)	-
Methyl-Isobutyl Ketone	2080 mg/kg	>10 mg/kg	-
N,N-DIMETHYL-P-TOLUIDINE	1650 mg/kg (rat)	2000 mg/kg (rat)	498 mL/m ³

Section 12 - Ecological information

Environmental data:

This product is readily biodegradable. Do not release into surface waters.

AQUATIC TOXICITY (ACUTE):

96-HOUR LC₅₀: > 220 mg/L (Golden orfe)

48-HOUR EC₅₀: > 500 mg/L (Daphnia)

96-HOUR EC₅₀: > 360 mg/L (green algae)

Section 13 - Disposal considerations

Disposal methods: Dispose of in accordance with local, State, and Federal regulations.

Section 14 - Transport information

DOT (Department of Transportation)

Proper shipping name: UN1173, ETHYL ACETATE, 3, II

AIR (ICAO/IATA)

Shipping name: ID800, SONSUMER COMMODITY, 9; or UN1173, ETHYL ACETATE, 3, II.

VESSEL (IMO/IMDG)

Shipping name: UN1173, ETHYL ACETATE, 3, II

Section 15 - Regulatory information

United States

SARA TITLE III (Superfund Amendments and Reauthorization Act)

Fire: Yes. **Pressure generating:** No. **Reactivity:** No. **Acute:** Yes. **Chronic:** No.

CERCLA (Comprehensive Response, Compensation, and Liability Act)

Chemical Name	Wt. %	CERCLA RQ
Ethyl acetate	85 - 100	5,000 lbs.
Methyl-Isobutyl Ketone	< 1	5,000

TSCA (Toxic Substance Control Act)

Chemical Name	CAS number:
Ethyl Acetate	141-78-6
Methyl-Isobutyl Ketone	107-87-9
Fragrance	108-10-1

TSCA status: All ingredients in this mixture are in compliance with TSCA.

CALIFORNIA PROPOSITION 65:



WARNING! This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name	Wt. %	LISTED
Methyl-Isobutyl Ketone	< 1	• Cancer • Developmental Toxicity
N,N-DIMETHYL-P-TOLUIDINE	< 1	• Cancer

General Comments:

Massachusetts Right To Know Components: Ethyl acetate (CAS 141078-6)

Pennsylvania Right To Know Components: Ethyl acetate (CAS 141078-6)

New Jersey Right To Know Components: Ethyl acetate (CAS 141078-6)

Section 16 - Other information

Approved by: Regulatory Department

Prepared by: Product Safety **Date Prepared:** 06/15/19


Hazardous Material Information System (U.S.A.)

Health	1
Flammability	3
Physical hazards	0
Personal protection	

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Kiara Sky Professional Nails Inc. does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.